

User Instructions (EN)

PHOTO WALLPAPER STANDARD ECO STRUCTURAL PHOTO WALLPAPER PREMIUM SAND STRUCTURAL PHOTO WALLPAPER PREMIUM CANVAS

Product description:

Producer: ARTTOR

Country of manufacture: Poland / Europe

PHOTO WALLPAPER STANDARD ECO		STRUCTURAL PHOTO WALLPAPER PREMIUM SAND		STRUCTURAL PHOTO WALLPAPER PREMIUM CANVAS	
Model / Overall size	Number of blocks	Model / Overall size	Number of blocks	Model / Overall size	Number of blocks
WF1AA100x70 / 100x70 cm	2	WF2AA100x70 / 100x70 cm	2	WF3AA100x70 / 100x70 cm	2
WF1AA150x105 / 150x105 cm	3	WF2AA150x105 / 150x105 cm	3	WF3AA150x105 / 150x105 cm	3
WF1AA200x140 / 200x140 cm	4	WF2AA200x140 / 200x140 cm	4	WF3AA200x140 / 200x140 cm	4
WF1AA250x175 / 250x175 cm	5	WF2AA250x175 / 250x175 cm	5	WF3AA250x175 / 250x175 cm	5
WF1AA300x210 / 300x210 cm	6	WF2AA300x210 / 300x210 cm	6	WF3AA300x210 / 300x210 cm	6
WF1AA350x256 / 350x256 cm	7	WF2AA350x256 / 350x256 cm	7	WF3AA350x256 / 350x256 cm	7
WF1AA400x280 / 400x280 cm	8	WF2AA400x280 / 400x280 cm	8	WF3AA400x280 / 400x280 cm	8
WF1AA450x315 / 450x315 cm	9	WF2AA450x315 / 450x315 cm	9	WF3AA450x315 / 450x315 cm	9
WF1AA500x350 / 500x350 cm	10	WF2AA500x350 / 500x350 cm	10	WF3AA500x350 / 500x350 cm	10

	PHOTO WALLPAPER STANDARD ECO	STRUCTURAL PHOTO WALLPAPER PREMIUM SAND	STRUCTURAL PHOTO WALLPAPER PREMIUM CANVAS
Weight	150g/m ²	290g/m ²	290g/m ²
Material	Uncoated synthetic paper	Vinyl	Vinyl
Underlay	Non-woven fabric	Non-woven fabric	Non-woven fabric
Fitting the blocks	Jointly - edge to edge	Jointly - edge to edge	Jointly - edge to edge

Photo wallpapers made individually according to the customer's design have dimensions and number of panels in accordance with the approved design.

Warnings and precautions:

Before starting the assembly, make sure you have the right tools and are able to perform the assembly yourself or with the help of an experienced person.

Manufacturer warranty:

- The manufacturer makes every effort to provide customers with a high-quality product.
- The manufacturer grants the buyer a 2-year warranty from the date of purchase of the product.
- Under the warranty, the Manufacturer is obligated to remove all defects resulting from manufacturing errors or material defects.

The manufacturer is not liable for defects resulting from:

- Modifications or changes to any elements.
- Improper installation, use or maintenance contrary to the intended use and instructions.
- Mechanical damage caused during use.

Content, technical and post-purchase support:

If you have any questions, concerns, problems or other issues related to the use and installation of the product, please contact your dealer or the manufacturer directly.



Warning, use the product as intended. The product is not a toy, may contain small, protruding parts. Keep out of reach of children.



The inks used during production meet environmental and health certificates enabling the products to be used in indoor spaces.



Do not leave the product near flammable materials.



The materials used to package our products are made from materials that can be recycled in accordance with our national environmental regulations.



Keep away from heat sources, in places not above or in the immediate vicinity of heat-emitting devices and equipment. The product should be placed in places not exposed to drafts.



Do not store in rooms exposed to high humidity.



Producer: Arttor Waldemar Błahyj i Leszek Błahyj Spółka Cywilna

Gostkowo 19, 87-148 Łysomice, POLAND,

NIP: PL8792621436, Regon: 340731016

e-mail: biuro@arttor.pl

Installation Instructions (EN)

Preparation:

1. Prepare the wall on which you want to stick the wallpaper:
 - Make sure the wall is dry, clean and free of grease.
 - Make sure the wall is free of holes. If there are any, they should be filled.
 - In the case of walls without any primer or paint coating (e.g. plasterboard, mineral plasters, gypsum plasters, concrete surfaces), they should be primed with an appropriate primer.
 - If the wall is covered with wallpaper – clean the wall of all layers of old wallpaper and then prime the wall.
 - If there are contrasting colours on the wall, it is recommended to use a light primer before wallpapering, which will even out the background colours and make it easier to evenly cover the wallpaper. This will make the wallpaper stick better and the pattern will not be disturbed by the intense colours of the base.
 - To obtain a perfect effect, the surface should be primed with an appropriate primer.
2. Unpack the wallpaper and check that the patterns on the rolls match when placed next to each other. If you notice that the pattern or color does not match the order, or the edges of the rolls do not match correctly, do not stick the wallpaper. In case of problems, contact the supplier. Complaints regarding inconsistencies will not be considered after it has been glued to the wall. Any irregularities should be reported before installation. **Do not start the wallpapering process until any doubts or discrepancies have been clarified.**
3. Prepare the materials and tools needed to install the wallpaper:
 - Non-woven wallpaper glue
 - Pencil, scissors, measuring tools
 - A glue brush and a tray for preparing the glue
 - Brush, wallpaper roller or flexible pressure roller
 - Sponge or cloth
4. It is not recommended to wallpaper in very dry or cold rooms, as this may negatively affect the drying process of the glue.
5. Before starting work, make sure that the glue is intended for non-woven wallpapers. The glue should be used according to the manufacturer's instructions and recommendations.

Post-assembly activities:

1. Check the adhesion of the wallpaper to the wall and the evenness of the glued stripes and pattern, assessing this from a distance of 1 to 2 meters.
2. Smooth the wallpaper again with a roller to remove any air bubbles. They should disappear within a few days.
3. Keep the room temperature above 10°C and ensure a constant supply of air for several days after wallpapering.
4. Avoid intense heating of wallpapered rooms and the use of air vents, which may accelerate the drying process of the wallpaper.

Safety Information



The manufacturer, Arttor Waldemar Błahyj and Leszek Błahyj Spółka Cywilna, informs that the manufactured product meets all safety requirements. The materials used for production are free from harmful substances and have been tested and certified in accordance with applicable standards, ensuring safe use in accordance with general safety regulations. Arttor has appointed Mr. Leszek Błahyj as the contact person for matters related to the product. For additional information or questions, please contact us at the following e-mail address: biuro@arttor.pl.

Installation:

1. After making sure that the wallpaper matches your order (in terms of quality, colours and pattern and edge matching), arrange the strips in the correct order according to their arrangement on the wall.
2. Marking the vertical and position of the wallpaper strips – using a long ruler, spirit level or ruler, mark vertical lines on the wall at intervals corresponding to the width of the wallpaper. These lines will serve as auxiliary markings, facilitating precise sticking.
3. Apply a thin, even layer of glue to the wall, in an area slightly wider than the width of the wallpaper strip. Do not apply glue directly to the wallpaper. Work systematically so that the glue does not dry before the wallpaper is applied.
4. Prepare the first strip of wallpaper, starting from the top. Roll the wallpaper inwards and make sure that the pattern is positioned correctly. Place the dry side of the wallpaper directly onto the adhesive on the wall, making sure that it adheres well to the surface. Gently place the wallpaper on the greased part of the wall. Slowly unroll the material so that it is evenly positioned along the previously prepared vertical lines on the wall (installation point 2).
5. Use a roller or brush to smooth the wallpaper and remove air bubbles. Move from the center of the strip outward, directing movements to the edges and up and down. Verify that the first strip is correctly positioned along the vertical auxiliary line, if necessary, move the wallpaper so that it is perfectly in the designated field.
6. After you have finished sticking, remove excess glue with a damp clean sponge or cloth. Do not rub too hard so as not to damage the wallpaper. Note! Each time you apply a strip of wallpaper, make sure that the pattern is properly aligned before the glue dries. Avoid rubbing the same place multiple times and do not use chemical cleaning agents, because the drying glue can damage the surface of the wallpaper.
7. Repeat the same action of applying wallpaper to the wall for the next strips, taking care to precisely match the pattern "butt joint". Remember that the strips are designed to fit together perfectly.
8. Use a wallpaper knife to cut off excess sections of wallpaper.
9. After installing the wallpaper, leave it to dry naturally for a few days. Do not rush this process to avoid damage and ensure that the wallpaper adheres properly to the wall.



Producer: Arttor Waldemar Błahyj i Leszek Błahyj Spółka Cywilna
Gostkowo 19, 87-148 Łysomice, POLAND,
NIP: PL8792621436, Regon: 340731016
e-mail: biuro@arttor.pl